

Data Sheet



Mini Angel 36DN Dome Camera

Technical Specification

Model	Mini Angel 36DN
CCD Sensor	1/3" Sony Super HAD CCD
Picture Pixels	NTSC: 510 (H) x 492 (V) PAL: 500 (H) x 582 (V)
Scanning System	NTSC standard 525 lines, 30 frames/sec PAL standard 625 lines, 25 frames/sec
Synchronous Mode	Internal
Horizontal Resolution	420 TV lines
Video Output	1.0Vp-p, 75Ohm, BNC connector
Gamma Characteristics	0.45
Electronic Shutter	NTSC: 1/60s ~ 1/100,000s PAL: 1/50s ~ 1/100,000s
Min. illumination	0.5 Lux @ F1.2 B&W 0.05 Lux @ F1.2
White Balance	Auto White Balance (2000°K ~ 10000°K)
Operation Environment	Operation Temperature: -10°C ~ +50°C Humidity: 0 ~ 95% RH
Storage Temp	-20°C ~ +80°C
Power Consumption	DC 12V / 110mA
Lens Options	4mm, 6mm, 8mm / F2.0



Note: Design and Specifications are subject to change without prior notice

Teleview Technologies Pte Ltd

65 Ubi Crescent #05-05, HOLA Centre Singapore 508559

Tel: +65 6289 1919 Fax: +65 6749 5759 Email: sales@teleview.com.sg URL: <http://www.teleview.com.sg>

Teleview Technologies LLC

16091 Swingley Ridge Road Suite 180 Chesterfield, MO 63017, U.S.A.

Tel: +01 63 653 22827 Fax: +01 63 653 27430 Email: sales@televiewtech.com URL: <http://www.televiewtech.com>