

## Data Sheet



### Mini Angel 36IR Dome Camera



### Technical Specification

Model	Mini Angel 36IR	
Signal System	PAL	NTSC
Number of Infrared LEDs	6	
Infra-red Distance coverage	10 – 12 Metres	
Imaging Device	1/3" SONY Super HAD CCD	
Lens	4.3mm (Other focal length also available)	
Camera Pixels	500 (H) × 582 (V)	510 (H) x 492 (V)
Sensing Area	4.9mm × 3.7mm	
Sync System Inter	Internal	
Scanning Mode	2:1 Interlaced	
Resolution	420 TV lines	
Minimum Illumination	0 LUX / F1.2	
Gain Control	Auto	
S/N Ratio	>48db(AGC OFF)	
White Balance	Auto Tracking White Balance	
Backlight Compensation	Auto	
Video Output	1.0 Vp-p75Ω	
Power Source	DC 12V	
Power Consumption	6 W	
Working Temperature	-10°C to +60°C	



Note: Design and Specifications are subject to change without prior notice

#### Teleview Technologies Pte Ltd

65 Ubi Crescent #05-05, Hola Centre Singapore 508559

Tel: +65 6289 1919 Fax: +65 6749 5759 Email: [sales@teleview.com.sg](mailto:sales@teleview.com.sg) URL: <http://www.teleview.com.sg>

#### Teleview Technologies LLC

16091 Swingley Ridge Road Suite 180 Chesterfield, MO 63017, U.S.A.

Tel: +01 63 653 22827 Fax: +01 63 653 27430 Email: [sales@televiewtech.com](mailto:sales@televiewtech.com) URL: <http://www.televiewtech.com>