

## Data Sheet



**Mini Angel 66DNVM  
Dome Camera**

### Technical Specification

Model	Mini Angel 66DNVM
CCD Sensor	1/3" Sony Super HAD CCD
Picture Pixels	NTSC: 768 (H) x 494 (V) PAL: 752 (H) x 582 (V)
Synchronous Mode	Internal
Horizontal Resolution	More than 520 TV lines
Video Output	1.0Vp-p, 75Ohm
Gamma Characteristics	0.45
Electronic Shutter	NTSC: 1/60s ~ 1/100,000s PAL: 1/50s ~ 1/100,000s
Min. illumination	0.5 Lux / F1.2 0.05 Lux / F1.2 (Monochrome Mode)
White Balance	Auto White Balance ( 2000°K ~ 10000°K )
Operation Environment	Operation Temperature: -10°C ~ +50°C Humidity: 0 ~ 95% RH
Storage Temp	-20°C ~ +80°C
Power Consumption	DC 12V / 110mA
Lens Options	3.5 mm to 8.0mm



Note: Design and Specifications are subject to change without prior notice

#### Teleview Technologies Pte Ltd

65 Ubi Crescent #05-05, HOLA Centre Singapore 508559

Tel: +65 6289 1919 Fax: +65 6749 5759 Email: [sales@teleview.com.sg](mailto:sales@teleview.com.sg) URL: <http://www.teleview.com.sg>

#### Teleview Technologies LLC

16091 Swingley Ridge Road Suite 180 Chesterfield, MO 63017, U.S.A.

Tel: +01 63 653 22827 Fax: +01 63 653 27430 Email: [sales@televiewtech.com](mailto:sales@televiewtech.com) URL: <http://www.televiewtech.com>