

Data Sheet



**Mini Angel 66DNVA2
Vandal Proof Dome Camera**

Technical Specification

Model	Mini Angel 66DNVA2	
Signal System	PAL	NTSC
Imaging Device	1/3"SONY Super HAD CCD	
Camera Pixels	795 (H) × 596 (V)	811 (H) × 508 (V)
Resolution	530 TV Lines	
Sensitivity (AGC on)	0.5 Lux @ F1.2 B/W 0.05 Lux @ F1.2	
S/N Ratio	> 55dB (AGC off, AESC off, Y sig)	
Auto Electronic shutter	1/50 (60) ~ 1/100,000 secs	
Backlight compensation	256 detection area + enhanced center compensation	
Auto Gain Control (AGC)	Up to 65 dB = ALC + Sample 32dB + DSP 28dB	
White Balance	Auto White Balance: 2400°K ~ 12000°K	
Synchronization	Internal	
Lens	Auto-Iris	
Video Output	1.0 Vp-p75Ω BNC	
Power Source	DC 12V	
Power Consumption	2W	
Casing Structure	Ultra hard grade aluminum with paint finish	
Dimension and Weight	146 (Ø) x 150 (H) mm, 875g	
Working Temperature	-10°C to +60°C	



Note: Design and Specifications are subject to change without prior notice

Teleview Technologies Pte Ltd

65 Ubi Crescent #05-05, Hola Centre Singapore 508559

Tel: +65 6289 1919 Fax: +65 6749 5759 Email: sales@teleview.com.sg URL: <http://www.teleview.com.sg>

Teleview Technologies LLC

16091 Swingley Ridge Road Suite 180 Chesterfield, MO 63017, U.S.A.

Tel: +01 63 653 22827 Fax: +01 63 653 27430 Email: sales@televiewtech.com URL: <http://www.televiewtech.com>